


TOYOTA

VEHICLE EMISSION CONTROL INFORMATION TOYOTA MOTOR CORPORATION

ENGINE FAMILY : JTY4.0T5FBB3 EVAP. FAMILY : EV-ME
EFI/ AI/ EGR/ O₂S/ TWC. 241.3 CID

MAKE ALL ADJUSTMENTS WITH ENGINE AT NORMAL OPERATING TEMPERATURE, AIR CLEANER INSTALLED, ALL ACCESSORIES TURNED OFF AND TRANSMISSION IN NEUTRAL, ENGINE TUNE - UP SPECIFICATIONS FOR ALL ALTITUDES

IGNITION TIMING (° BTDC)	7° WITH THE CHECK CONNECTOR SHORT - CIRCUITED AT IDLING. CHECK CONNECTOR	
DASH POT SETTING SPEED(RPM)	1200 WITH ISC CONNECTOR DISCONNECTED AND WITH VENT HOLE OF DASH POT PLUGGED. (SEE REPAIR MANUAL FOR ADDITIONAL INFORMATION)	
VALVE CLEARANCE	INTAKE 0.008 IN. (0.20MM) EXHAUST 0.014 IN. (0.35MM)	
IDLE MIXTURE SETTING	IDLE MIXTURE SCREW IS PRESET AND SEALED AT FACTORY. ADJUSTMENT DURING TUNE - UP IS NOT RECOMMENDED.	
IDLE SPEED AND FAST IDLE SPEED	N/A (AUTOMATICALLY CONTROLLED)	

THIS VEHICLE CONFORMS TO U.S. EPA AND STATE OF CALIFORNIA REGULATIONS APPLICABLE TO 1988 MODEL YEAR NEW LIGHT - DUTY TRUCKS.


61050 3F-E CAL CATALYST N7

TOYOTA

VEHICLE EMISSION CONTROL INFORMATION TOYOTA MOTOR CORPORATION

ENGINE FAMILY : JTY4.0T5FBB3 EVAP. FAMILY : EV-ME
EFI/ AI/ EGR/ O₂S/ TWC. 241.3 CID

MAKE ALL ADJUSTMENTS WITH ENGINE AT NORMAL OPERATING TEMPERATURE, AIR CLEANER INSTALLED, ALL ACCESSORIES TURNED OFF AND TRANSMISSION IN NEUTRAL, ENGINE TUNE - UP SPECIFICATIONS FOR ALL ALTITUDES

IGNITION TIMING (° BTDC)	7° WITH THE CHECK CONNECTOR SHORT - CIRCUITED AT IDLING. CHECK CONNECTOR	
DASH POT SETTING SPEED(RPM)	1200 WITH ISC CONNECTOR DISCONNECTED AND WITH VENT HOLE OF DASH POT PLUGGED. (SEE REPAIR MANUAL FOR ADDITIONAL INFORMATION)	
VALVE CLEARANCE	INTAKE 0.008 IN. (0.20MM) EXHAUST 0.014 IN. (0.35MM)	
IDLE MIXTURE SETTING	IDLE MIXTURE SCREW IS PRESET AND SEALED AT FACTORY. ADJUSTMENT DURING TUNE - UP IS NOT RECOMMENDED.	
IDLE SPEED AND FAST IDLE SPEED	N/A (AUTOMATICALLY CONTROLLED)	

THIS VEHICLE CONFORMS TO U.S. EPA REGULATIONS APPLICABLE TO 1988 MODEL YEAR NEW LIGHT - DUTY TRUCKS.

61040 3F-E FED CATALYST N6

CAUTION
REMOVE FUEL CAP SLOWLY
FUEL SPRAY MAY CAUSE INJURY

**WASHER
LAVE-GLACE**

CAUTION
SYSTEM TO BE SERVICED BY QUALIFIED PERSONNEL ONLY. IMPROPER SERVICE METHODS MAY CAUSE PERSONAL INJURY. CONSULT SERVICE MANUAL. S.A.E. J3023
REFRIGERANT UNDER CHARGE R134a
HIGH PRESSURE MAX 1.65 lb (0.75 kg) MIN 1.32 lb (0.6 kg)
NIPPONDENSO CO., LTD. JAPAN

CAUTION
SYSTEM TO BE SERVICED BY QUALIFIED PERSONNEL ONLY. IMPROPER SERVICE METHODS MAY CAUSE PERSONAL INJURY. CONSULT SERVICE MANUAL. S.A.E. J-639
REFRIGERANT UNDER CHARGE R-12
HIGH PRESSURE MAX 1.65 lb (0.75 kg) MIN 1.32 lb (0.6 kg)
NIPPONDENSO CO., LTD. JAPAN

荒川車体工業最高です
ARAKAWA AUTO BODY

AIR CLEANER SERVICE
REPLACE ELEMENT
EVERY 30,000 MILES (48,000km)
OR 36 MONTHS.
CLEAN ELEMENT FOR NORMALLY
DRIVING ON DUSTY ROADS
EVERY 5,000 MILES (8,000km)
OR 6 MONTHS.

ENGINE OIL & OIL FILTER SERVICE
REPLACE ENGINE OIL & OIL FILTER
UNDER NORMAL CONDITION
EVERY 10,000 MILES (16,000km)
OR 12 MONTHS.
UNDER SEVERE CONDITION
EVERY 5,000 MILES (8,000km)
OR 6 MONTHS.

OVERDRIVE

**UNLEADED
FUEL ONLY**

R
TOYOTA
25870-61020
139000-2600
Q
DENSO
MADE IN JAPAN

Notice
Due to excessive heat build up, this fan will be running after the engine is stopped. It will automatically turn off within 30 minutes.

TOYOTA
25620-61110
135000-2840
EGRV
DENSO
MADE IN JAPAN

TOYOTA
25710-61030
135200-1270
ASV
DENSO
MADE IN JAPAN

Notice
Due to excessive heat build up, this fan will be running after the engine is stopped. It will automatically turn off within 30 minutes.

