

2.0 SERIES VALVING SPECIFICATIONS

COMPRESSION DAMPING

VALVE OUTSIDE DIA.	#30	#35	#40	#45	#50	#55	#60	#65	#70	#75	#80	#85	#90
1.600"	0.008	0.008	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015
1.425"	0.008	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015
1.350"	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015
1.100"	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015
.950"	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015
.800"	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020

REBOUND DAMPING

VALVE OUTSIDE DIA.	#30	#35	#40	#45	#50	#55	#60	#65	#70	#75	#80	#85	#90
1.425"	0.008	0.008	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015
1.350"	0.008	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015
1.100"	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015
.950"	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015
.800"	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015
.750" BACK UP	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200



Apparently when Fox refers to "60/40" shock it means: 60% of the available compression damping / 40% of the available rebound damping.
See the separate notes in Mac Pages for notes pertaining to this from Sam and my overhaul and valving session on 12-16-09